



# SHANGHAI NYTEX COMPOSITES

TEL:021-59573168 FAX:021-59573707  
http://www.nytex.com.cn

## Product Information

## NYLOY<sup>®</sup> KF-0030N R811WS

• Nylon • Electrical insulative thermal conductive  
toughness flame retardant • White

PROPERTY	METHOD	UNIT	RESULT
<b>MECHANICAL</b>			
Tensile Strength	ASTM D638	kg/cm <sup>2</sup> (MPa)	420 (41.1)
Elongation	ASTM D638	%	4.5
Flexural Strength	ASTM D790	kg/cm <sup>2</sup> (MPa)	900 (88.2)
Flexural Modulus	ASTM D790	kg/cm <sup>2</sup> (MPa)	50000 (4902.0)
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm (J/M)	4.5 (37.2)
<b>THERMAL</b>			
Heat Deflection Temp (4.6kg/cm <sup>2</sup> ) (0.46MPa)	ASTM D648	°C	185
Conductivity	ISO 22007-2	W/m*K	1
<b>ELECTRICAL</b>			
Surface Resistance	ASTM D257	Ohm-P-SQ	>1E+12
<b>OTHER</b>			
Density	ASTM D792	g/cm <sup>3</sup>	1.69
Mold Shrinkage	ASTM D955		
// flow		%	0.4
⊥ flow		%	0.8
Flammability	UL-94	3.2mm	V0
<b>REMARK</b>			
(1)This data is for reference only.			