



SHANGHAI NYTEX COMPOSITES

TEL:021-59573168 FAX:021-59573707
http://www.nytex.com.cn

Product Information

NYLOY[®] KF-0030N R811BS

- Nylon
- Electrical insulative thermal conductive
- flame retardant
- Black

PROPERTY	METHOD	UNIT	RESULT
MECHANICAL			
Tensile Strength	ASTM D638	kg/cm ² (MPa)	400 (39.2)
Elongation	ASTM D638	%	6
Flexural Strength	ASTM D790	kg/cm ² (MPa)	750 (73.5)
Flexural Modulus	ASTM D790	kg/cm ² (MPa)	38000 (3725.5)
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm (J/M)	4.5 (44.1)
THERMAL			
Heat Deflection Temp (4.6kg/cm ²) (0.46MPa)	ASTM D648	°C	180
Conductivity	ISO 22007-2	W/m*K	0.8
ELECTRICAL			
Surface Resistance	ASTM D257	Ohm-P-SQ	>1E+12
Electric Breakdown Voltage	Nytex Method	KV	>10
OTHER			
Density	ASTM D792	g/cm ³	1.57
Mold Shrinkage	ASTM D955		
// flow		%	0.7
⊥ flow		%	1.2
Flammability	UL-94	3.2mm	V0
REMARK			
(1)This data is for reference only.			