



# SHANGHAI NYTEX COMPOSITES

TEL:021-59573168 FAX:021-59573707  
http://www.nytex.com.cn

## Product Information

## NYLOY<sup>®</sup> CT-0010N-V R601W2

- PC
- Electrical insulative thermal conductive
- flame retardant
- White

PROPERTY	METHOD	UNIT	RESULT
<b>MECHANICAL</b>			
Tensile Strength	ASTM D638	kg/cm <sup>2</sup> (MPa)	420 (41.2)
Elongation	ASTM D638	%	7
Flexural Strength	ASTM D790	kg/cm <sup>2</sup> (MPa)	750 (73.6)
Flexural Modulus	ASTM D790	kg/cm <sup>2</sup> (MPa)	30000 (2944.1)
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm (J/M)	6 (58.8)
<b>THERMAL</b>			
Heat Deflection Temp (4.6kg/cm <sup>2</sup> ) (0.46MPa)	ASTM D648	°C	110
Conductivity	ISO 22007-2	W/m*K	0.7
<b>ELECTRICAL</b>			
Surface Resistance	IEC 60093	Ohm-P-SQ	>1E+12
Electric Breakdown Voltage	Nytex Method	KV	>10
<b>OTHER</b>			
Density	ASTM D792	g/cm <sup>3</sup>	1.44
Mold Shrinkage	ASTM D955	%	0.35
Flammability	UL-94	1.6mm	V0
<b>REMARK</b>			
(1)This data is for reference only.			