



SHANGHAI NYTEX COMPOSITES

TEL:021-59573168 FAX:021-59573707
http://www.nytex.com.cn

Product Information

NYLOY[®] KF-0030N 301BLT

• Nylon • Electrical insulative thermal conductive
halogen-free flame retardant • Black

PROPERTY	METHOD	UNIT	RESULT
MECHANICAL			
Tensile Strength	ASTM D638	kg/cm ² (MPa)	525 (51.5)
Elongation	ASTM D638	%	1.5
Flexural Strength	ASTM D790	kg/cm ² (MPa)	920 (90.2)
Flexural Modulus	ASTM D790	kg/cm ² (MPa)	72000 (7058.8)
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm (J/M)	3.0 (29.4)
THERMAL			
Heat Deflection Temp (4.6kg/cm ²) (0.46MPa)	ASTM D648	°C	205
Conductivity	ISO 22007-2	W/m*K	1.0
ELECTRICAL			
Surface Resistance	ASTM D257	Ohm-P-SQ	>1E+12
OTHER			
Density	ASTM D792	g/cm ³	1.605
Mold Shrinkage	ASTM D955		
// flow		%	0.4
⊥ flow		%	0.7
Flammability	UL-94	3.2mm	V0
REMARK			
(1)This data is for reference only.			