



# SHANGHAI NYTEX COMPOSITES

TEL:021-59573168 FAX:021-59573707  
http://www.nytex.com.cn

## Product Information

## NYLOY<sup>®</sup> CM-5000 8045B2

• Nylon • Thermal and electrical conductive flame retardant grade • Black

PROPERTY	METHOD	UNIT	RESULT
<b>MECHANICAL</b>			
Tensile Strength	ASTM D638	kg/cm <sup>2</sup>	900
Elongation	ASTM D638	%	1.3
Flexural Strength	ASTM D790	kg/cm <sup>2</sup>	1400
Flexural Modulus	ASTM D790	kg/cm <sup>2</sup>	135000
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm	5.0
<b>THERMAL</b>			
Heat Deflection Temp (18.6kg/cm <sup>2</sup> ) (1.82MPa)	ASTM D648	°C	205
Conductivity	ISO 22007-2	W/m*K	4.5
<b>ELECTRICAL</b>			
Surface Resistance	ASTM D4496	Ohm-P-SQ	10 <sup>5</sup>
<b>OTHER</b>			
Density	ASTM D792	g/cm <sup>3</sup>	1.52
Mold Shrinkage	ASTM D955		
// flow		%	0.2
⊥ flow		%	0.4
Flammability	UL-94	3.2mm	V0
<b>REMARK</b>			
(1)This data is for reference only.			